


**Caracteristici:**

|           |       |        |
|-----------|-------|--------|
| <b>Di</b> | 60 mm |        |
| <b>B</b>  | 60 mm | Latime |
| <b>Do</b> | 65 mm |        |

|                          |        |                                                                          |
|--------------------------|--------|--------------------------------------------------------------------------|
|                          |        | Recommended mounting tolerance:<br>Shaft<br>h8<br><br>Housing bore<br>H7 |
| <b>2)</b>                |        | Lubrication pocket                                                       |
| <b>C<sub>i min</sub></b> | 0,2 mm |                                                                          |
| <b>d<sub>L</sub></b>     | 6 mm   |                                                                          |
| <b>1)</b>                |        | Joint gap                                                                |
| <b>C<sub>i max</sub></b> | 1 mm   |                                                                          |
| <b>C<sub>o</sub></b>     | 1,8 mm | Tolerance: +/-0,6                                                        |
| <b>s<sub>3</sub></b>     | 2,5 mm |                                                                          |
| <b>Di</b>                | 60 mm  |                                                                          |
| <b>Do</b>                | 65 mm  |                                                                          |

|          |       |                                                                      |
|----------|-------|----------------------------------------------------------------------|
| <b>m</b> | 224 g | Masa                                                                 |
|          |       | Bushes in special sizes available by agreement.                      |
|          |       | Deformation of lubrication hole due to roll rounding is permissible. |